

TOUCH POS SYSTEM SP-3500

ELEGANCE AND FLEXIBILITY AT POINT OF SALE



The new Partner Tech SP-3500 POS system combines elegance and flexibility with powerful, energy efficient technology. This grants a future proved investment SP-3500 Series design, with sleek and elegant appearance, is available with different monitor sizes.

Both monitors, either 11.6" or 15.6", provide PCT (Multi Touch) technology, plus it's adjustable and foldable arm design allows flexible use in every Point-of-Sale environment.

Furthermore the SP-3500 systems come with a variety of peripherals to be integrated. The options include Magnetic stripe reader (MSR), Fingerprint sensor, IC card reader, NFC (RFID) reader, 2D scanner, camera and wireless module.

The combination of the functionalities makes the SP-3500 Series a clever choice for POS solutions of today's changing business environments.

SPECIAL FEATURES

Foldable design with different monitor selection
15.6" or 11.6"

Projected Capacitive Touch (PCT)

Supports up to 8GB RAM

Wide range of interfaces, incl. USB 3.0

2nd monitor support

Spill and dust resistant front panel, IP 66

OPTIONAL

Mini PCI-e, e.g. to support WiFi module

2nd monitor support (7", 11.6" or 15")

3-track MSR, Smart Card reader,
NFC / RFID reader, FingerPrint sensor,
2D scanner, Camera (2.0M)

SP-3500

ITEM	SP-3511	SP-3515
CPU	Intel® Celeron™ J1900 (2.00GHz up to 2.42GHz), quad core, 2MB L2 Cache, fanless	
LCD	Bezelfree 11.6" TFT-LCD, resolution 1366 x 768, brightness 350cd/m2, LED backlight	Bezelfree 15.6" TFT-LCD, resolution 1366 x 768, brightness 350cd/m2, LED backlight
Touch	Projected Capacitive Touch (Multi Touch) with USB interface	
RAM	DDR3 SO-DIMM, 2 slots up to 8GB	
LAN	1 x RJ-45 10/100/1000 BASE-T Gigabit Ethernet	
Storage	1 x 2.5" SATA HDD or SSD (option)	
I/O Interface	4 x COM (DC+0/5/12V: COM 1-2 BIOS selection, COM 3-4 by jumper) 5 x USB 2.0 1 x USB 3.0 1 x PS/2 1 x RJ-45 Ethernet 1 x RJ-11 Cash drawer control (for 2 cash drawers) 1 x VGA 1 x DC + 12V Out 1 x Mini PCI-e (internal) 1 x 12V, 1x 24V powered USB (option)	
Speaker	2 x 3W speaker (internal)	
Operating System	Windows 7, POSReady 7, Windows 8.1, Windows 10, Linux (ubuntu)	
Power Supply	AC100~240V/DC+12V, 7.5A, 90W power adaptor	
Dimensions	302mm (W) x 298mm (D) x 369mm (H)	390mm (W) x 298mm (D) x 401mm (H)
Environment	Operating Temperature: 0°C ~ +40°C Humidity: 15% ~ 80%	Storage Temperature: -20°C ~ +60°C Humidity: 15% ~ 80%
Option	3-track MSR, Smart card reader, LF/HF NFC/RFID reader, Fingerprint sensor, 2D Barcode reader, front Camera 2.0 MP, SSD	
Color	black or white	

*Specification is subject of change without prior notice



Choice of monitor size, Compact and small foot print



Flexible design allows wide range of usability's in Point of Sale